

OPERATION SHEET

HUSQVARNA 820 GRINDER

SAFETY/RISK/HAZARD ASSESSMENT

PLANT INFORMATION

NHG Ref/Part No. GRINDHUS

Plant Name: Grinder – Husqvarna 820

Potential Noise Level in Db: 90 – 95db

Required hearing protection class: 2

Operator Competency: Plant Licence Not Required

It is the hirer's responsibility to ensure that all operators are

competent.

Please refer to the User Guide and Operators Manual for

detailed Operating Instructions





RISK ASSESSMENT INFORMATION

Potential Hazard(s)

Electrocution

Risk Level Low

Control Measures Avoid having body contact with lightning-conductors and metal in the ground.

Exposure to ultraviolet radiation if working outdoors

Risk Level Medium

Control Measures Wear sunscreen, hat, long sleeves and long pants.

Injury

Risk Level Medium/Low

Control Measures Ensure hands, feet and loose clothing are kept clear from moving parts of the

power tool. Do not remove guards or covers.

Do not operate equipment under the influence of alcohol or drugs

Beware of debris ejected from the work piece.

Ensure leads are stowed safely and does not present a trip hazard

Ensure the switch is in the off position before connecting to power source and/or

battery pack, picking up or carrying the tool.

III health due to dust inhaled

Risk Level Medium

Control Measures Always provide for good ventilation. Use an approved dust mask to avoid inhaling

excessive amount of dust formed whilst grinding.

Hearing Damage

Risk Level Low

Control Measures Hearing protection with a rating of 20Db must be worn.

Please refer to the User Guide and Operators Manual for detailed Operating Instructions

The safety information contained in this assessment is general information only and should not be relied upon as a substitute for professional advice or tuition, which the hirer should seek before operating.