

OPERATION SHEET

DISABLED TOILET ON TRAILER

SAFETY/RISK/HAZARD ASSESSMENT

PLANT INFORMATION

NHG Ref/Part No. TLTDIS

Plant Name: Disabled Toilet - R56 639 – Blue/SR - Green

Operator Competency: Plant Licence Not Required

IS YOUR VEHICLE CAPABLE OF TOWING THIS TRAILER?

It is the drivers responsibility to check vehicle manufacturers towing specifications for braked and unbraked maximum loadings and are adhered to. This also includes all on road legal requirements.





RISK ASSESSMENT INFORMATION

Page 1 of 2 TLTDIS

Potential Hazard(s)

Accident

Risk Level High

Control Measures During setup, wear appropriate PPE (safety footwear and Hi-Vis jacket)

Beware of tipping when turning or on uneven ground

Check that the trailer towbar and connections are not damaged

Ensure jockey wheel is properly positioned for parking or retracted for travel

Ensure stabilisers are retracted when travelling

Ensure wheels are chocked and brake applied when parked

Ensure steps are retracted before travelling

Ensure door is fully secure before starting journey

Steps to be locked in stowed position

Care to be taken when lowering steps to avoid leg injury

Ensure rear drain cover is latched before travel

Ensure unit is on solid and level ground

Avoid prolonged occupation in hot weather

Avoid contact with stored contents

Please refer to the User Guide and Operators Manual for detailed Operating Instructions

The safety information contained in this assessment is general information only and should not be relied upon as a substitute for professional advice or tuition, which the hirer should seek before operating.