

SAFETY/RISK/HAZARD ASSESSMENT

PLANT INFORMATION

NHG Ref/Part No.

TLTDBL1

Plant Name:

Double Toilet - V36 136 - Tin

Operator Competency:

Plant Licence Not Required

IS YOUR VEHICLE CAPABLE OF TOWING THIS TRAILER?

It is the drivers responsibility to check vehicle manufacturers towing specifications for braked and unbraked maximum loadings and are adhered to. This also includes all on road legal requirements.



Protective
equipment
must be worn
when operating
this machine



RISK ASSESSMENT INFORMATION

Potential Hazard(s)

Accident

Risk Level	High
Control Measures	Wear appropriate PPE (safety footwear and Hi-Vis jacket) Beware tipping of board when turning or on uneven ground Check that the trailer towbar and connections are not damaged Ensure jockey wheel is properly positioned for parking or retracted for travel Ensure stabilisers are retracted when travelling Ensure wheels are chocked and brake applied when parked Ensure steps are retracted before travelling Ensure door is fully secure before starting journey Steps to be locked in stowed position Care to be taken when lowering step to avoid leg injury Ensure rear drain cover is latched before travel Ensure unit is on solid and level ground Avoid prolonged occupation in hot weather Avoid contact with stored contacts

**Please refer to the User Guide and Operators Manual
for detailed Operating Instructions**

The safety information contained in this assessment is general information only and should not be relied upon as a substitute for professional advice or tuition, which the hirer should seek before operating.