

OPERATION SHEET

DRUM ROLLER 1.2T

SAFETY/RISK/HAZARD ASSESSMENT

PLANT INFORMATION

NHG Ref/Part No.

Plant ID: RD 12

Plant Name: 1.2 tonne Drum Roller

Operator Competency: Plant Licence Not Required















RISK ASSESSMENT INFORMATION

Potential Hazard(s)

Crush injury

Risk Level High

Control Measures Keep unauthorised persons away from site

Check rotating beacon and reversing alarm devices daily

Only operate machine whilst sitting in seat with belt on

Do not allow inexperienced persons to operate machinery. Do not allow persons

to sit or ride on the machine.

Fuel leaks and fire hazards

Risk Level Medium

Control Measures Check fuel lines and fuel level daily. Engine needs to be turned off before refuelling.

Keep a fire extinguisher on the machine.

Exposure to ultraviolet radiation if working outdoors

Risk Level Medium

Control Measures Wear sunscreen, hat, long sleeves and long pants.

Rollover of machine or falling of machine

Risk Level Medium/Low

Control Measures Reinforce ground, edges and shoulders

Do not operate close to steep inclines or in sloppy material

Roller to be lifted only at designated lifting points

Hearing Damage

Risk Level Low

Control Measures Hearing protection with a rating of 20Db must be worn.

<u>Burns</u>

Risk Level Low

Control Measures Keep other persons away from hot machine

Allow to cool down before doing any checks on the engine.

KEY OPERATING INSTRUCTION

Please refer to the User Guide and Operators Manual for detailed Operating Instructions

The safety information contained in this assessment is general information only and should not be relied upon as a substitute for professional advice or tuition, which the hirer should seek before operating.