

Assessment Number: 1		Assessment Date: 18/6/20
Plant Type: Plaster Sander Plant Make: Giraffe Plant Model: AG700 550w		Assessment Facilitated by: Leigh Evans (Admin/Accounts Manager)
Asset/Fleet/Rego No: PLASANDER Plant Serial No.		Assessment Participants: Lachlan Horton (Yard Manager)
Plant Owner Name: Northern Hire Group		Initial Assessment
Follow up based on change to:		
Use of plant ☐ System of work ☐ Plant En	vironment [□ New or additional information □ Plant through modification □
Is the plant designed to perform the task?	es X No [
Has the plant been modified from the original condition?	es 🗌 No 🕽	X
Is the plant in good working condition and free of weeds & Ye mud?	es X No [
All identified action items closed out/addressed (plant checks)?	es X No [
Is the plant safe to operate? (On completion of PHA and action closure)	es X No [
		Date: Signature:

Revision No: 1



Risk / Opportunity Rating Table (see <u>Risk Management Consultation</u>
<u>Process Appendix</u> for a full description of Risk Consequence, Opportunity Consequence and Likelihood Ratings)

	Almost Certain	D	С	В	Α	Α				
ting	Likely	D	D	С	В	A				
Likelihood rating	Possible	Е	D	С	С	В				
Likeli	Unlikely	E	E	D	С	В				
	Rare	E	E	D	D	С				
		1	2	3	4	5				
		Consequence rating								

Action and Approval Scheme

These suggested timings and tolerance levels in the Action Table will be overridden by specific policies of the company that either dictate shorter timeframes for corrective action or zero tolerance. For example, the company has a zero tolerance policy for Safety and Environmental risks.

The decision to tolerate a risk or capture a opportunity should be based on a consideration of:

Whether the risk / opportunity is being controlled to a level that is reasonably achievable;

Whether it would be cost-effective to further control risk or capture the opportunity;

Whether user wishes to tolerate risks / opportunities of that type

Action Table

Residual risk / opp level	Suggested action	Timing of status report and management plans	Authority for continued toleration or improvement of residual rating.
A	Take action to eliminate or implement additional controls to reduce it to acceptable level (ALARP/SFAIRP). "Onsite activities" — Intolerable and activity must not commence	Report as soon as practicable. Normally within hours.	Senior Executive Manager Plus Project Manager / Project Leadership Team
В	Implement additional controls reduce it to ALARP/SFAIRP. "Onsite activities" – must not commence without Corporate Management review	Manage and re-evaluate risk / opportunity to allow reporting days Manage and re-evaluate risk / opportunity to allow reporting every two weeks	General Manager and / or Project Manager / Project Leadership Team
С	Implement additional controls reduce it to ALARP/SFAIRP. "Onsite activities" – must not commence without Site Management review	Manage and re-evaluate risk / opportunity to allow reporting monthly	"Specialist" Manager, eg Construction or Design Manager
D	Will still require attention within existing operations to reduce to ALARP/SFAIRP. "Onsite Activities" – Site Management must determine appropriate level of management and supervision prior to commencement of activity	Manage and re-evaluate risk / opportunity to allow reporting every quarter	Team Leader
E	Lower priority. May be tolerable	Monitor, manage and carryout activity in accordance with identified controls	Supervisor

Revision No: 1

Issue Date: 18/6/2020



Potential Hazards	ŀ	Haza		Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk Level	New or Additional Controls Action By:	Action Verified as Complete: (Name and
	Υ	N	N/ A				on Plant	2010.	(Name and Date)	Date)
Are there any specific warnings or conditions (manufacturers or other) relating to potential hazards from the operation of the item of plant?	Y			Potential Hazard	Refer to Safety Instructions on Pages 2-3 of Operator Manual					
 Refer to technical or operating manuals, SOPs, safe use instructions List any relevant safety warning hazards & controls 					risk assessment should be conducted to determine safe placement					
2. Are there any COMMUNICATION requirements in relation to the safe operation of the plant?		N								
 Active signalling processes. Point to point communications. Whistle Spotter (with/without whistles) Flag signalling Labels and signage 										
3. Can anyone be ENTANGLED in the plant?	Υ			Potential Hazard	Refer to Safety Instructions on Pages 2-3 of Operator Manual					
 Hair or other body parts caught in moving parts PPE caught in moving parts Isolation devices Warning decals Guarding Rotating parts Emergency stops 										

Revision No: 1 Page 3 of 16

Issue Date: 18/6/2020



Potential Hazards	Y	Hazaı N	N/ A	Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required on Plant	Final Risk Level	New or Additional Controls Action By: (Name and Date)	Action Verified as Complete: (Name and Date)
4. Can anyone be CRUSHED or TRAPPED? (e.g. through unexpected movement, lack of capability for plant or equipment to be slowed, stopped or immobilised, plant tipping or rolling, being thrown from plant)		N	_ A							
 Emergency stop (E Stop) Service or parking brake Battery isolator ROPs/FOPs Being crushed between moving parts Unexpected movement Neutral Start Reversing/travel alarm Warning horn Amber flashing beacon Rear swing warning lights Pedals non slip surface Appropriate controls Rear view mirror Seat belt Door inter locks Crush zone decals Guarding devices Mandatory secondary protection device installed on all boomtype MEWP 										

Revision No: 1 Page 4 of 16



		Hazaı	rd				New or Additional		New or Additional	Action Verified
Potential Hazards	Υ	N	N/ A	Describe Hazard	Controls	Current Risk Level	Controls Required on Plant	Final Risk Level	Controls Action By: (Name and Date)	as Complete: (Name and Date)
5. Can anyone be CUT, STABBED or PUNCTURED?		N								
 Flying objects Moving parts Pinch points Sharp edges Isolation devices Warning decals Guarding 										
Between two moving and rotating parts Between fixed and moving parts Warning decals Guarding	Y			Potential Hazard	Refer to Safety Instructions on Pages 2-3 of Operator Manual					
7. Can ABRASION, TEARING or STRETCHING occur? Continuous contact with moving parts Warning decals Guarding Pulling/pushing	Y			Potential hazard	Refer to Safety Instructions on Pages 2-3 of Operator Manual					
8. Can anyone be STRUCK whilst operating the plant? Plant disintegrating Mobility of plant travelling Reversing/travel alarm Amber flashing beacon Work pieces thrown out Moving parts Warning decals Guarding		N								

Revision No: 1

Page 5 of 16



Potential Hazards		Hazard				Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk	New or Additional Controls Action By: (Name and Date)	Action Verified as Complete:
	Υ	N	N/ A	Describe Hazaru	Controls	Carront flick 2010.	on Plant	Level	(Name and Date)			
9. Can a hazardous PRESSURE be produced?		N										
Hydraulic hosesRadiatorCome into contact with fluids under high pressure												

Revision No: 1

When printed this document is an uncontrolled version and must be checked against the IMS electronic version for validity



Potential Hazards	ı	Hazaı		Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk	New or Additional Controls Action	Action Verified as Complete:
	Υ	N	N/ A				on Plant	Level	By: (Name and Date)	(Name and Date)
10. Can an ELECTRICAL hazard be created? Lack of insulation Contact with electrical conductors Poor earthing Water near equipment Lack of isolation Warning decals	Y	N		Potential Hazard	Sander is designed for DRY USE ONLY. Refer to Safety Instructions on Pages 2-3 of Operator Manual Check power lead daily and do not use if signs of wear or damage detected. Ensure the power source is		on Plant		(Name and Date)	Date)
				connected to an RCD (safety switch), and that the lead and connections are protected from moisture.						
					Exclusion zones and PPE (goggles, mask, protective clothing) will be required and a site specific risk assessment must be undertaken to determine PPE and controls					

Revision No: 1

Page 7 of 16

Issue Date: 18/6/2020



Page 8 of 16

Potential Hazards	Y	Hazar N	N/	Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required on Plant	Final Risk Level	New or Additional Controls Action By: (Name and Date)	Action Verified as Complete: (Name and Date)
11. Can an EXPLOSION or LOSS OF CONTENTS occur?		N	Α						(Name and Date)	
 Gas emission, Dusts Vapours, lubricants Fuel tank Storage of haz chemicals/ DG's near plant Warning decals Ejection of workpiece Collapse or fragmentation 										
12. Can anyone using or near the plant SLIP, TRIP or FALL?		N								
Uneven surfaceFall from a heightWeather conditionsSlippery surfaces										
13. Are there ERGONOMIC - MANUAL HANDLING hazards associated with the plant? Poor posture Repetitive or sustained movements Awkward positions Strained movements Poorly designed seating Access and egress Access for maintenance Routine inspections and adjustments	Y			Potential Hazard	Refer to Safety Instructions on Pages 2-3 of Operator Manual					

Revision No: 1

When printed this document is an uncontrolled version and must be checked against the IMS electronic version for validity.



Potential Hazards		lazar	rd N/	Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required on Plant	Final Risk Level	New or Additional Controls Action By:	Action Verified as Complete: (Name and
14. Are there ERGONOMIC - OPERATING CONTROL hazards associated with the plant?	Υ	N N	Α				OH Flank		(Name and Date)	Date)
 Difficult to understand Inappropriate colouring Function not identified Inappropriate controls & switches Access and egress Labelling of controls and indicators Variation in operators Operation by two or more persons 										
15. Are there specific requirements for ISOLATION of energy sources? Hydraulic pressure		N								
 Compressed gases Electrical feeds/capacitors Motive power systems Suspended loads Operation by two or more persons 										
16. Can unplanned LOSS of POWER create a hazard?		N								
 Engine shutdown Loss of electrical supply Loss of steering systems Ability to apply brakes and stop Ability to lower suspended loads 										

Revision No: 1

Issue Date: 18/6/2020

Page 9 of 16



Potential Hazards	ı	Hazaı		Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk Level	New or Additional Controls Action By:	Action Verified as Complete: (Name and
	Υ	N	N/ A				on Plant	Level	(Name and Date)	Date)
17. Can anyone be SUFFOCATED?		N								
 Lack of oxygen Contaminated atmosphere Confined spaces Spaces where air flow is inadequate 										
18. Does operation of the plant cause extreme TEMPERATURE changes?		N								
 Fire Burns through conduction Convection Cryogenic burns Operation in extreme heat or cold 										
 19. Can a FIRE occur? Friction Ingress of materials/fluids Build-up of materials/lubricants Fuels Fire extinguisher 		N								
 20. Can certain WEATHER conditions create a hazard? Hypothermia / extreme cold Heat stroke / extreme hot Wet conditions Electrical storms Dirt & mud on roads at egress 	Y			Potential Hazard	Refer to Safety Instructions on Pages 2-3 of Operator Manual Avoid using outdoors during inclement weather.					
points					Refer to local weather forecasts					

Revision No: 1

Page 10 of 16



Potential Hazards	ŀ	Hazar		Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk	New or Additional Controls Action	Action Verified as Complete:
	Υ	N	N/ A				on Plant	Level	By: (Name and Date)	(Name and Date)
21. Does VIBRATION of the plant create a hazard? Plant becomes unstable Causes physical problems for the operator whilst operating Vibration of equipment Operation could cause unacceptable vibration levels in nearby structures	Y		A	Potential Hazard with prolonged use	Avoid overreaching & use sander with both hands at all times. User recommended to take regaulr breaks to avoid muscle fatigue.					
22. Can the plant emit toxic FUMES or VAPOURS? Exhaust fumes Chemicals Haz chemicals/DG's		N			muscie rangue.					
23. Carry out NOISE survey on page 14. Is the plant noisy? Emit >85 dBA at the operator Effects operator communication Noise impacts on community during out-of-hours work (including reversing beepers)			N/ A							
24. Carry out the LIGHT survey on page 14. Is there poor visibility At the controls At the task Darkens surrounding areas Light impacts on community or sensitive natural environment during out-of-hours work			N/ A							

Revision No: 1

Page 11 of 16



H	lazar		Describe Hazard Control	Controls		New or Additional Controls Required	Final Risk Level	New or Additional Controls Action By:	Action Verified as Complete: (Name and
Υ	N	N/ A				on Plant	Level	(Name and Date)	(Name and Date)
	N								
Y			Potential Hazard	Prolonged breathing of airborne dust					
				may affect respiratory function.					
				Always use a vacuum and wear a respirator approved for					
				DO NOT sand surfaces which may contain lead based paints					
				Care is to be taken when disposing of dust.					
				A job specific assessment must be undertaken by client onsite to determine PPE					
		N	N	Y N A N	Y N A Potential Hazard Prolonged breathing of airborne dust may affect respiratory function. Always use a vacuum and wear a respirator approved for dust. DO NOT sand surfaces which may contain lead based paints Care is to be taken when disposing of dust. A job specific assessment must be undertaken by	Y N N N Potential Hazard Prolonged breathing of airborne dust may affect respiratory function. Always use a vacuum and wear a respirator approved for dust. DO NOT sand surfaces which may contain lead based paints Care is to be taken when disposing of dust. A job specific assessment must be undertaken by client onsite to determine PPE	Y N A Potential Hazard Prolonged breathing of airborne dust may affect respiratory function. Always use a vacuum and wear a respirator approved for dust. DO NOT sand surfaces which may contain lead based paints Care is to be taken when disposing of dust. A job specific assessment must be undertaken by client onsite to determine PPE	Y N N A Potential Hazard Prolonged breathing of airborne dust may affect respiratory function. Always use a vacuum and wear a respirator approved for dust. DO NOT sand surfaces which may contain lead based paints Care is to be taken when disposing of dust. A job specific assessment must be undertaken by client onsite to determine PPE	Y N A Potential Hazard Prolonged breathing of airborne dust may affect respiratory function. Always use a vacuum and wear a respirator approved for dust. DO NOT sand surfaces which may contain lead based paints Care is to be taken when disposing of dust. A job specific assessment must be undertaken by client orsite to determine PPE

Revision No: 1

Page 12 of 16

Issue Date: 18/6/2020



Potential Hazards		Hazard N/		Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required on Plant	Final Risk Level	New or Additional Controls Action By:	Action Verified as Complete: (Name and
	Υ	N	A				on Plant		(Name and Date)	Date)
27. Can the plant become UNSTABLE during operation?		N								
 Working on uneven / unstable ground Shifting load Lack of plant support Outriggers 										
28. Could LOSS of LOAD occur?		N								
 Failure of ropes/slings Overloading Entanglement in surrounding structures Maintenance requirements 										
29. Is there anything in the SURROUNDING ENVIRONMENT that may produce a hazard?		N								
 Power lines Low ceiling Other plant Storage areas Co-located equipment Isolation requirements Potential for flash flooding if operating adjacent to waterways 										
Operating in known areas of weeds, pathogens or contamination Operating in sensitive environments requiring protection from offsite weeds/pathogens or spills										

Revision No: 1 Page 13 of 16

Issue Date: 18/6/2020



Potential Hazards	ŀ	Hazard		Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk	New or Additional Controls Action	Action Verified as Complete: (Name and
	Υ	N	N/ A				on Plant	Level	By: (Name and Date)	Date)
 30. Can CHEMICALS create a hazard? Leaking from plant Splashing Explosion PPE considerations Spill kit considerations 	Y			Potential Hazard	Never use the sander near flammable solids, liquids or gases. Sparks could cause a fire or explosion.					
31. Operator TRAINING / QUALIFICATIONS? Training requirements Qualification requirements Competency assessments Documentation Operator's manual Equipment experience Product knowledge			N/ A							
32. Are there ANY OTHER potential hazards generated by or during the use of this item of plant and/or any attachments?		N								

ALL OPERATORS OF THE PLANT OR EQUIPMENT MUST BE BRIEFED ON THE PLANT HAZARD ASSESSMENT (PHA) PRIOR TO FIRST TIME USE.

ANY RELEVANT CONDITIONS WHICH MAY IMPACT ON THE OPERATION OF THIS ITEM OF PLANT OR EQUIPMENT MUST BE TRANSFERRED TO THE AMS/TRA.

Revision No: 1 Page 14 of 16



NOISE REPORT							
Equipment Type:	Plaster Sander	Serial/Asset No.	I/Asset No. PLASAN				
Make:	Giraffe	Model:	AG700				
Test by (print):	Leigh Evans	Date:	0				
Signature:							
Sound Level Meter U	Jnit Used:						
Manufactures specif	fied noise level:		92-103 dBA				
Background level:				dBA			
Results - Operator's	Station	103 dBA High Idle					
(Equipment Operating	ng)	92	dBA	Low Idle			
Comments:							
must be worn at all t		nel) is over 90 dB(A). I py when the unit is ru loss.					
must be worn at all t comply may result in Results – Bystander	times within the canon hearing damage or Position:	py when the unit is ru loss.	nning. F				
must be worn at all t comply may result in Results – Bystander At 7 metres from sid	times within the canon hearing damage or Position:	py when the unit is ru	nning. F	ailure to			
must be worn at all t comply may result in Results – Bystander At 7 metres from sid Front	times within the canon hearing damage or Position:	py when the unit is ru loss.	nning. F	ailure to			
must be worn at all t comply may result in Results – Bystander At 7 metres from sid	times within the canon hearing damage or Position:	py when the unit is ru loss.	nning. F	ailure to			
must be worn at all t comply may result in Results – Bystander At 7 metres from sid Front	times within the canon hearing damage or Position:	py when the unit is ru loss.	nning. F	ailure to			
must be worn at all t comply may result in Results – Bystander At 7 metres from sid Front Rear	times within the canon hearing damage or Position:	py when the unit is ru loss.	nning. F	dBA			
must be worn at all t comply may result in Results – Bystander At 7 metres from sid Front Rear Left	times within the canon hearing damage or Position:	py when the unit is ru loss.	nning. F	dBA dBA dBA			
must be worn at all t comply may result in Results – Bystander At 7 metres from sid Front Rear Left Right	times within the canon hearing damage or Position:	py when the unit is ru loss.	nning. F	dBA dBA dBA			
must be worn at all t comply may result in Results – Bystander At 7 metres from sid Front Rear Left Right	times within the canon hearing damage or Position:	py when the unit is ru loss.	nning. F	dBA dBA dBA			
must be worn at all t comply may result in Results – Bystander At 7 metres from sid Front Rear Left Right	times within the canon hearing damage or Position:	py when the unit is ru loss.	nning. F	dBA dBA dBA			

LIGHTING REPORT				
Test by (print):		Date:		
Signature:				
Lux Meter used:				
Results - Operator's station				
At controls				Lux
At emergency control				Lux
In front/over task				Lux
Left side task				Lux
Right side task				Lux
Comments:				
Results – Surroundings:				
Clearly seen by others?		□ Yes	□ No	
Decrease lighting in walkways	?	□ Yes	□ No	
Decrease lighting to other wor	kstations?	□ Yes	□ No	
Comments:				

Revision No: 1

Page 15 of 16



COMMENTS:

Revision No: 1

Page 16 of 16