

Assessment Number: 1			Assessment Date: 16/6/20
Plant Type: Vibrating Plate Compactor Plant Make: Crommelins Plant Model: CC60R/70R/90R/92R			Assessment Facilitated by: Leigh Evans (Admin/Accounts Manager)
Asset/Fleet/Rego No: VIBL Plant Serial No.			Assessment Participants: Lachlan Horton (Yard Manager)
Plant Owner Name: Northern Hire Group			Initial Assessment
Follow up based on change to: Use of plant System of work Plant	t Environme	ent 🗌	New or additional information ☐ Plant through modification ☐
, _			
Is the plant designed to perform the task?	Yes X	No 🗆	
Has the plant been modified from the original condition?	Yes 🗌	No X	
Is the plant in good working condition and free of weeds & mud?	Yes X	No 🗆	
All identified action items closed out/addressed (plant checks)?	Yes X	No 🗆	
Is the plant safe to operate? (On completion of PHA and action closure)	Yes X	No 🗆	
			Date: Signature:

Revision No: 2

Page 1 of 20



Risk / Opportunity Rating Table (see <u>Risk Management Consultation</u>
<u>Process Appendix</u> for a full description of Risk Consequence, Opportunity Consequence and Likelihood Ratings)

	Almost Certain	D	С	В	Α	A			
ting	Likely	D	D	С	В	Α			
Likelihood rating	Possible	E	D	С	С	В			
Likeli	Unlikely	E	E	D	С	В			
	Rare	Е	Е	D	D	С			
		1	2	3	4	5			
		Consequence rating							

Action and Approval Scheme

These suggested timings and tolerance levels in the Action Table will be overridden by specific policies of the company that either dictate shorter timeframes for corrective action or zero tolerance. For example, the company has a zero tolerance policy for Safety and Environmental risks.

The decision to tolerate a risk or capture a opportunity should be based on a consideration of:

Whether the risk / opportunity is being controlled to a level that is reasonably achievable;

Whether it would be cost-effective to further control risk or capture the opportunity;

Whether user wishes to tolerate risks / opportunities of that type

Action Table

Residual risk / opp level	Suggested action	Timing of status report and management plans	Authority for continued toleration or improvement of residual rating.
A	Take action to eliminate or implement additional controls to reduce it to acceptable level (ALARP/SFAIRP). "Onsite activities" — Intolerable and activity must not commence	Report as soon as practicable. Normally within hours.	Senior Executive Manager Plus Project Manager / Project Leadership Team
В	Implement additional controls reduce it to ALARP/SFAIRP. "Onsite activities" – must not commence without Corporate Management review	Manage and re-evaluate risk / opportunity to allow reporting days Manage and re-evaluate risk / opportunity to allow reporting every two weeks	General Manager and / or Project Manager / Project Leadership Team
С	Implement additional controls reduce it to ALARP/SFAIRP. "Onsite activities" – must not commence without Site Management review	Manage and re-evaluate risk / opportunity to allow reporting monthly	"Specialist" Manager, eg Construction or Design Manager
D	Will still require attention within existing operations to reduce to ALARP/SFAIRP. "Onsite Activities" – Site Management must determine appropriate level of management and supervision prior to commencement of activity	Manage and re-evaluate risk / opportunity to allow reporting every quarter	Team Leader
E	Lower priority. May be tolerable	Monitor, manage and carryout activity in accordance with identified controls	Supervisor

Revision No: 2

Issue Date: 16/6/2020



Potential Hazards			d	Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk	New or Additional Controls Action	Action Verified as Complete:
	Υ	N	N/ A				on Plant	Level	By: (Name and Date)	(Name and Date)
1. Are there any specific warnings or conditions (manufacturers or other) relating to potential hazards from the operation of the item of plant? Refer to technical or operating manuals, SOPs, safe use instructions List any relevant safety warning hazards & controls	Y			Potential Hazard	Refer to attached Safety Instructions or pages 3 of Operator Manual & site specific controls					
Are there any COMMUNICATION requirements in relation to the safe operation of the plant? Active signalling processes. Point to point communications. Whistle Spotter (with/without whistles) Flag signalling Labels and signage	Y			Potential Hazard	Refer to attached Safety Instructions or pages 3 of Operator Manual & site specific controls					

Revision No: 2 Page 3 of 20



Potential Hazards	ı	Hazaı	ď	Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk	New or Additional Controls Action	Action Verified as Complete:
	Υ	N	N/ A				on Plant	Level	By: (Name and Date)	(Name and Date)
3. Can anyone be ENTANGLED in the plant? Hair or other body parts caught in moving parts PPE caught in moving parts Isolation devices Warning decals Guarding Rotating parts Emergency stops	Y			Entanglement risk from moving parts	Exclusion zones and PPE (steel cap boots, goggles, mask, protective clothing) will be required and a siet specific risk assessment must be undertaken to determine PPE and controls. Machine must be isolated before cleaning or maintenance. Body parts and loose items such as jewellery, fabric, strapping, cables, wires etc. to be kept clear of moving parts					

Issue Date: 16/6/2020



Potential Hazards	Υ	Haza	rd N/	Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required on Plant	Final Risk Level	New or Additional Controls Action By:	Action Verified as Complete: (Name and
4. Can anyone be CRUSHED or TRAPPED? (e.g. through unexpected movement, lack of capability for plant or equipment to be slowed, stopped or immobilised, plant tipping or rolling, being thrown from plant) Emergency stop (E Stop) Service or parking brake Battery isolator ROPs/FOPs Being crushed between moving parts Unexpected movement Neutral Start Reversing/travel alarm Warning horn Amber flashing beacon Rear swing warning lights Pedals non slip surface Appropriate controls Rear view mirror Seat belt Door inter locks Crush zone decals Guarding devices Mandatory secondary protection device installed on all boomtype MEWP	Y		A	Serious injury from contact with plant	Isolate plant before commencing pre-start. Identify delineation between site personnel and plant. Exclusion zones will be required and a site specific risk assessment must be undertaken onsite to determine extent of controls Refer to transport load restraint guide or transport SOP/SWMS to determine proper securing of device.				(Name and Date)	Date)

Revision No: 2 Page 5 of 20



Potential Hazards	ŀ	lazar		Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk Level	New or Additional Controls Action By:	Action Verified as Complete: (Name and
	Υ	N	N/ A				on Plant	Level	(Name and Date)	Date)
5. Can anyone be CUT, STABBED or PUNCTURED? Flying objects Moving parts Pinch points Sharp edges Isolation devices Warning decals Guarding	Y			Potental injury from ejected materials	Pre-start inspection must ensure all guards are in place. Exclusion zones and PPE (goggles, mask, protective clothing) will be required and a risk assessment must be undertaken onsite to determine PPE and controls.					
Between two moving and rotating parts Between fixed and moving parts Warning decals Guarding	Y			Body parts can be sheared between two parts of the plant, or plant and structure/obstacle while in operation	Exclusion zones and PPE (goggles, mask, protective clothing) will be required and a risk assessment must be undertaken onsite to determine PPE and controls. Machine must be isolated before cleaning or maintenance					



Potential Hazards	H	Hazar		Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk	New or Additional Controls Action	Action Verified as Complete:
	Υ	N	N/ A				on Plant	Level	By: (Name and Date)	(Name and Date)
 7. Can ABRASION, TEARING or STRETCHING occur? Continuous contact with moving parts Warning decals Guarding Pulling/pushing 	Y			Injury caused by contact with moving parts	Exclusion zones and PPE (steel cap boots goggles, mask, protective clothing) will be required and a risk assessment must be undertaken onsite to determine PPE and controls. Machine must be isolated before cleaning or maintenance					
8. Can anyone be STRUCK whilst operating the plant? Plant disintegrating Mobility of plant travelling Reversing/travel alarm Amber flashing beacon Work pieces thrown out Moving parts Warning decals Guarding	Y			Operator and/or workers/public struck by plant and/or debris	Exclusion zones and PPE (goggles, mask, protective clothing) will be required and site specific a risk assessment must be undertaken to determine PPE and controls.					

When printed this document is an uncontrolled version and must be checked against the IMS electronic version for validity

Issue Date: 16/6/2020



Potential Hazards	Hazard		rd	Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk	New or Additional Controls Action	Action Verified as Complete:
1 otomar nazaras	Υ	N	N/ A	Describe Hazard	Controls	ourient riisk zever	on Plant	Level	By: (Name and Date)	(Name and Date)
 9. Can a hazardous PRESSURE be produced? Hydraulic hoses Radiator Come into contact with fluids under high pressure 	Y			Potential Hazard	Ensure that a sturdy, permanent shield is installed to prevent injury due to fluid leakage or component failure. Once installed this shield(s) must be present and fully functional at all times whilst this item of plant is in operation.					



10. Can an ELECTRICAL hazard be created? Lack of insulation Contact with electrical conductors Poor earthing Water near equipment Lack of isolation Warning decals	Y		Contact wih overhead and/or underground electrical services	Determine location of overhead and underground hazards and clearly mark above ground with minimum approach distances. These distances must be adhered to strictly. Spotters are required when working within 5 motion of the			
				working within 5 metres of the minimum approach distance of any live electrical apparatus. Any encroach within the minimum approach distances must only occur if the following provisions have been met – 1. The machine is designed to work within the minimum approach distances 2. Permission has been granted by the electricity company and			
				3. Safe systems of work have been documented and approved.			

Revision No: 2



Potential Hazards	I	Hazaı		Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk	New or Additional Controls Action	Action Verified as Complete:
	Υ	N	N/ A				on Plant	Level	By: (Name and Date)	(Name and Date)
					Establish exclusion zone.					
11. Can an EXPLOSION or LOSS OF CONTENTS occur? Gas emission, Dusts Vapours, lubricants Fuel tank Storage of haz chemicals/DG's near plant Warning decals Ejection of workpiece Collapse or fragmentation	Y			Potential Hazard	Please refer to Operator Manual					
 12. Can anyone using or near the plant SLIP, TRIP or FALL? Uneven surface Fall from a height Weather conditions Slippery surfaces 	Υ			Potential Hazard	A site specific risk assessment must be undertaken by client prior to operating plant					
13. Are there ERGONOMIC - MANUAL HANDLING hazards associated with the plant? Poor posture Repetitive or sustained movements Awkward positions Strained movements Poorly designed seating Access and egress Access for maintenance Routine inspections and adjustments	Y			Potential Hazard	Refer to attached Safety Instructions or page 3 of Operator Manual & site specific controls					

Revision No: 2

Issue Date: 16/6/2020

Page 10 of 20



Potential Hazards	ŀ	Hazaı		Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk	New or Additional Controls Action	Action Verified as Complete:
	Υ	N	N/ A				on Plant	Level	By: (Name and Date)	(Name and Date)
14. Are there ERGONOMIC - OPERATING CONTROL hazards associated with the plant? Difficult to understand Inappropriate colouring Function not identified Inappropriate controls & switches Access and egress Labelling of controls and indicators Variation in operators Operation by two or more persons	Y			Potential Hazards - Strains	All controls including all levers, buttons, pedals, switches etc, are placed near the operator work position and are easy to reach and operate during the execution of the operator's normal duties. This applies for all persons within the 95th percentile of the normal population distribution.					
15. Are there specific requirements for ISOLATION of energy sources? Hydraulic pressure Compressed gases Electrical feeds/capacitors Motive power systems Suspended loads Operation by two or more persons	Y			Potential Hazard	All controls including all levers, buttons, pedals, switches etc. are clearly labelled as to their purpose and method of operation. These labels must be maintained in a clean and serviceable condition at all times					



Potential Hazards	ŀ	Hazard				Describe Hazard	Controls Curr	Current Risk Level	New or Additional Controls Required	Final Risk Level	New or Additional Controls Action	Action Verified as Complete:
	Υ	N	N/ A				on Plant	By: (Name and Date)	(Name and Date)			
16. Can unplanned LOSS of POWER create a hazard?	Y			Potential Hazard	Please refer to Operator Manual							
 Engine shutdown Loss of electrical supply Loss of steering systems Ability to apply brakes and stop Ability to lower suspended loads 												
17. Can anyone be SUFFOCATED?		N										
 Lack of oxygen Contaminated atmosphere Confined spaces Spaces where air flow is inadequate 												
18. Does operation of the plant cause extreme TEMPERATURE changes?		N										
Fire Burns through conduction Convection Cryogenic burns Operation in extreme heat or cold												



Potential Hazards	ı	Haza		Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk	New or Additional Controls Action	Action Verified as Complete:
	Υ	N	N/ A				on Plant	Level	By: (Name and Date)	(Name and Date)
 19. Can a FIRE occur? Friction Ingress of materials/fluids Build-up of materials/lubricants Fuels Fire extinguisher 	Y			Potential Hazard	Fire extinguisher(s) to AS 1841 must be present on worksite and fully functional and serviceable at all times. They must be readily accessible to the operator. Regular inspections must also be carried out in accordance with the manufacturer's requirements and AS 1851					
20. Can certain WEATHER conditions create a hazard? Hypothermia / extreme cold Heat stroke / extreme hot Wet conditions Electrical storms Dirt & mud on roads at egress points	Y			Potential Hazard	Please refer to Operator Manual					
21. Does VIBRATION of the plant create a hazard? Plant becomes unstable Causes physical problems for the operator whilst operating Vibration of equipment Operation could cause unacceptable vibration levels in nearby structures	Y			Potential Hazard to operator over prolonged use	Modify work methods to reduce exposure					

Revision No: 2

Issue Date: 16/6/2020

Page 13 of 20



Potential Hazards	ŀ	Hazar	ď	Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk	New or Additional Controls Action	Action Verified as Complete:
	Υ	N	N/ A	Describe Hazara	Controls	Garrett Hisk Eever	on Plant	Level	By: (Name and Date)	(Name and Date)
22. Can the plant emit toxic FUMES or VAPOURS?	Y			Potential Hazard from exhaust fumes	Do not use in enclosed spaces.					
Exhaust fumesChemicalsHaz chemicals/DG's					Ensure adequate ventilation					
23. Carry out NOISE survey on page 14. Is the plant noisy?	Y			Potential hazard with prolonged use	A site specific risk assessment must be undertaken to					
 Emit >85 dBA at the operator Effects operator communication Noise impacts on community during out-of-hours work (including reversing beepers) 					determine PPE and controls.					
24. Carry out the LIGHT survey on page 14. Is there poor visibility			N/ A							
At the controls At the task Darkens surrounding areas Light impacts on community or sensitive natural environment during out-of-hours work										
25. Does the plant emit RADIATION?		N								
Eg X-raysEMRLaser										

Revision No: 2 Page 14 of 20



Potential Hazards	ı	Haza	rd	Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk	New or Additional Controls Action	Action Verified as Complete:
	Υ	N	N/ A				on Plant	Level	By: (Name and Date)	(Name and Date)
26. Can operation of the plant create DUST? Explosive atmosphere Breathing hazard Reduced visibility Nuisance dust at nearby community Impact on local flora and fauna Loss of topsoil and spread of weeds and pathogens	Y			Exposure to hazardous dust	Site risk assessment must be undertaken by client to ensure hazardous dust is not disturbed by plant/task (e.g. asbestos) Exclusion zones and PPE (goggles, mask, protective clothing) will be required and a risk assessment must be undertaken onsite to determine PPE and controls					
 27. Can the plant become UNSTABLE during operation? Working on uneven / unstable ground Shifting load Lack of plant support Outriggers 	Y			Potential Hazard	A site specific risk assessment must be undertaken by client onsite to determine PPE and controls					
28. Could LOSS of LOAD occur? Failure of ropes/slings Overloading Entanglement in surrounding structures Maintenance requirements	Y			Potential Hazard	Refer to Operator manual for pre- operational checks, maintenance & load capacity					

Issue Date: 16/6/2020



Potential Hazards	ŀ	Hazard		Describe Hazard	Controls C	Current Risk Level	New or Additional Controls Required	Final Risk Level	New or Additional Controls Action	Action Verified as Complete:
	Υ	N	N/ A				on Plant	Level	By: (Name and Date)	(Name and Date)
29. Is there anything in the SURROUNDING ENVIRONMENT that may produce a hazard? Power lines Low ceiling Other plant Storage areas Co-located equipment Isolation requirements Potential for flash flooding if operating adjacent to waterways Operating in known areas of weeds, pathogens or contamination	Y			Potential Hazard	A site specific risk assessment must be undertaken by client to detemine controls, PPE & exclusion zones.					
Operating in sensitive environments requiring protection from offsite weeds/pathogens or spills										
 30. Can CHEMICALS create a hazard? Leaking from plant Splashing Explosion PPE considerations Spill kit considerations 	Y			Potential Hazard	Please refer to Operator Manual.					

Revision No: 2 Page 16 of 20



Potential Hazards	ŀ	Hazar		Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk	New or Additional Controls Action	Action Verified as Complete:
	Υ	N	N/ A				on Plant	Level	By: (Name and Date)	(Name and Date)
31. Operator TRAINING / QUALIFICATIONS? Training requirements Qualification requirements Competency assessments Documentation Operator's manual Equipment experience Product knowledge	Y			Operation by persons who are not suitably qualified or experienced may result in injury to person, damage to property, and may also void insurance cover.	This equipment may only be moved and operated by persons who are suitably qualified/experie nced and who have been appointed by the contractor for driving and servicing the earth moving machinery. All operators must completely read and understand the Operator Manual prior to operating plant. Undertake a Job Safety and Environmental Analysis before use of plant, and use to determine that the relevant safety procedures are in place before commencing work.					
32. Are there ANY OTHER potential hazards generated by or during the use of this item of plant and/or any attachments?	Y			Plant Failure	Pre – Operational Inspection	D	DAILY - Operators must complete Start-up checklist Operation checklist Parking Checklist	E		

Revision No: 2

Page 17 of 20



ALL OPERATORS OF THE PLANT OR EQUIPMENT MUST BE BRIEFED ON THE PLANT HAZARD ASSESSMENT (PHA) PRIOR TO FIRST TIME USE.

ANY RELEVANT CONDITIONS WHICH MAY IMPACT ON THE OPERATION OF THIS ITEM OF PLANT OR EQUIPMENT MUST BE TRANSFERRED TO THE AMS/TRA.

Revision No: 2

Issue Date: 16/6/2020

Page 18 of 20



NOISE REPORT			
Equipment Type:	Vibrating Plate Compactor	Serial/Asset No.	VIBL
Make:	Crommelins	Model:	CC60R/70R/90R/ 92R
Test by (print):	Leigh Evans	Date:	16/6/20
Signature:			
Sound Level Meter Ur	nit Used:		
Manufactures specifie	ed noise level:		67 dBA
Background level:			ВА
Results - Operator's	Station	67	dBA High Idle
(Equipment Operating	g)		dBA Low Idle
Comments:			
Results – Bystander I			
At 7 metres from side	of equipment – Equip	ment Operating (High	gh Idle)
Front			dBA
Rear			dBA
Left			dBA
Right			dBA
Comments:			

LIGHTING REPORT				
Test by (print):		Date:		
Signature:				
Lux Meter used:				
Results - Operator's station				
At controls				Lux
At emergency control				Lux
In front/over task				Lux
Left side task				Lux
Right side task				Lux
Comments:				
Describe Occurrent discrete				
Results – Surroundings:				
Clearly seen by others?		□ Yes	□ No	
Decrease lighting in walkways	?	□ Yes	□ No	
Decrease lighting to other wor	kstations?	□ Yes	□ No	
Comments:				

Revision No: 2

Page 19 of 20



COMMENTS:	

Revision No: 2

Page 20 of 20