

SAFETY/RISK/HAZARD ASSESSMENT

PLANT INFORMATION

NHG Ref/Part No.	PUMSUB1
Plant ID:	CRS5456
Plant Name:	Toolkwip LA4A 50mm Submersible Pump 240V
Potential Noise Level in Db:	80 to less than 105
Required hearing protection class:	3
Operator Competency:	Plant Licence Not Required



Protective
equipment
must be worn
when operating
this machine



RISK ASSESSMENT INFORMATION

Potential Hazard(s)

Electrocution

Risk Level Medium

Control Measures Electricity and water are a hazardous combination. Do not use if cable is damaged. Do not leave pump unattended. Switch off and remove the plug from the socket before removing from water source.

Exposure to ultraviolet radiation if working outdoors

Risk Level Medium

Control Measures Wear sunscreen, hat, long sleeves and long pants.

Injury from contact with moving parts

Risk Level Low

Control Measures All moving parts are protected. Do not remove guards or covers.

KEY OPERATING INSTRUCTIONS

1. Lower and lift pump by rope attached to the lifting ring. Do not lift by the electrical cable.
2. Do not leave pump unattended
3. Keep suction inlets on the pump clear of mud and debris
4. Turn off pump at mains and remove plug from socket before lifting it out of the water.

**Please refer to the User Guide and Operators Manual
for detailed Operating Instructions**

The safety information contained in this assessment is general information only and should not be relied upon as a substitute for professional advice or tuition, which the hirer should seek before operating.