

frequency. Inspections should be more frequent for equipment operating in a continuous daily manner or under harsh conditions.



Toro TX1000 Pre-Operational Checks

To be undertaken by the operator <u>each day</u> before first use:

1.	Engine and hydraulic oil levels.	
2.	Inspect all components to ensure	
	they are attached securely.	
3.	Hydraulic oil, engine oil or fuel	
	leakage (look for fresh oil stains on	
	ground) and for pipes and hoses to be	
	secured to prevent damage.	
4.	Inspect arm assembly area for firm	
	attachment & sufficient lubrication.	
	Grease/oil pivot points and moving	
	parts where applicable.	
5.	Chassis – check for visible damage.	
6.	Condition and tension of chains and	
	sprockets (if applicable)	
7.	Fuel level.	
8.	Exhaust for damage/holes that may	
	contribute to excessive noise.	
9.	Wheel drive motor assemblies & all	
	controls, linkages and cables to be	
	free from damage and operate	
	smoothly and freely (eg. Engine	
	speed, forward/reverse, luffing and	
	slewing, steering controls).	
	Travel brakes are operational.	
11.	Visually check stress areas such as	
	hooks, chains, pivots, tracks for signs	
	of cracking & fatigue.	
	Routine inspections should be carried	
Check Performed By:		
Date:	/ /	

out at no greater than 3 monthly