

Assessment Number: 1	Assessment Date: 18/3/20
Plant Type: Twin Drum Roller Plant Make: Dynapac Plant Model: CC1200vi	Assessment Facilitated by: Leigh Evans (Admin/Accounts Manager)
Asset/Fleet/Rego No: 1NT6YT Plant Serial No. VIV 100000395HJA022493	Assessment Participants: Lachlan Horton (Yard Manager)
Plant Owner Name: Northern Hire Group	Initial Assessment
Follow up based on change to:	
Use of plant ☐ System of work ☐ Plant Environment ☐	New or additional information Plant through modification
Is the plant designed to perform the task? Yes X No	
Has the plant been modified from the original condition? Yes No. 1	X
Is the plant in good working condition and free of weeds & $$ Yes X $$ No mud?	
All identified action items closed out/addressed (plant Yes X No checks)?	
Is the plant safe to operate? (On completion of PHA and $$\operatorname{Yes} X$$ No action closure)	
	Date: Signature:

Revision No: 1

Page 1 of 21



Risk / Opportunity Rating Table (see <u>Risk Management Consultation</u>
<u>Process Appendix</u> for a full description of Risk Consequence, Opportunity Consequence and Likelihood Ratings)

	Almost Certain	D	С	В	Α	A			
ting	Likely	D	D	С	В	Α			
Likelihood rating	Possible	E	D	С	С	В			
Likeli	Unlikely	E	E	D	С	В			
	Rare	Е	E	D	D	С			
		1	2	3	4	5			
		Consequence rating							

Action and Approval Scheme

These suggested timings and tolerance levels in the Action Table will be overridden by specific policies of the company that either dictate shorter timeframes for corrective action or zero tolerance. For example, the company has a zero tolerance policy for Safety and Environmental risks.

The decision to tolerate a risk or capture a opportunity should be based on a consideration of:

Whether the risk / opportunity is being controlled to a level that is reasonably achievable;

Whether it would be cost-effective to further control risk or capture the opportunity;

Whether the user wishes to tolerate risks / opportunities of that type

Action Table

Residual risk / opp level	Suggested action	Timing of status report and management plans	Authority for continued toleration or improvement of residual rating.
A	Take action to eliminate or implement additional controls to reduce it to acceptable level (ALARP/SFAIRP). "Onsite activities" — Intolerable and activity must not commence	Report as soon as practicable. Normally within hours.	Senior Executive Manager Plus Project Manager / Project Leadership Team
В	Implement additional controls reduce it to ALARP/SFAIRP. "Onsite activities" – must not commence without Corporate Management review	Manage and re-evaluate risk / opportunity to allow reporting days Manage and re-evaluate risk / opportunity to allow reporting every two weeks	General Manager and / or Project Manager / Project Leadership Team
С	Implement additional controls reduce it to ALARP/SFAIRP. "Onsite activities" – must not commence without Site Management review	Manage and re-evaluate risk / opportunity to allow reporting monthly	"Specialist" Manager, eg Construction or Design Manager
D	Will still require attention within existing operations to reduce to ALARP/SFAIRP. "Onsite Activities" – Site Management must determine appropriate level of management and supervision prior to commencement of activity	Manage and re-evaluate risk / opportunity to allow reporting every quarter	Team Leader
E	Lower priority. May be tolerable	Monitor, manage and carryout activity in accordance with identified controls	Supervisor

Revision No: 1

Issue Date: 4/7/2019



Potential Hazards	ı	Hazar	ď	Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk	New or Additional Controls Action	Action Verified as Complete:
	Υ	N	N/ A				on Plant	Level	By: (Name and Date)	(Name and Date)
1. Are there any specific warnings or conditions (manufacturers or other) relating to potential hazards from the operation of the item of plant? Refer to technical or operating manuals, SOPs, safe use instructions List any relevant safety warning hazards & controls	Y			Potential Hazard	Refer to attached Safety Instructions or pages 5-10 of Operator Manual & site specific controls					
Are there any COMMUNICATION requirements in relation to the safe operation of the plant? Active signalling processes. Point to point communications. Whistle Spotter (with/without whistles) Flag signalling Labels and signage	Y			Potential Hazard	Refer to attached Safety Instructions or pages 5-10 of Operator Manual & site specific controls					

Revision No: 1 Page 3 of 21



Potential Hazards	ŀ	Hazar		Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk	New or Additional Controls Action	Action Verified as Complete:
- otomar nazarao	Υ	Ν	N/ A			Carront flick zovol	on Plant	Level	By: (Name and Date)	(Name and Date)
3. Can anyone be ENTANGLED in the plant? Hair or other body parts caught in moving parts PPE caught in moving parts Isolation devices Warning decals Guarding Rotating parts Emergency stops	Y			Entanglement risk from moving parts	Exclusion zones and PPE (goggles, mask, protective clothing) will be required and a siet specific risk assessment must be undertaken to determine PPE and controls. Machine must be isolated before cleaning or maintenance. Body parts and loose items such as jewellery, fabric, strapping, cables, wires etc. to be kept clear of moving parts					

Revision No: 1 When printed this document is an uncontrolled version and must be checked against the IMS electronic version for validity

Issue Date: 4/7/2019



				T		
4. Can anyone be	Y	Death or serious injury from	Ensure that all			
CRUSHED or		unexpected movement of plant	operators follow			
TRAPPED? (e.g.			approved			
through unexpected			SWMS/ SOP			
movement, lack of			when loading			
capability for plant or			and unloading			
equipment to be			this machine to			
slowed, stopped or			and from a flat			
immobilised, plant			top truck or			
tipping or rolling, being			trailer, low loader or tilt tray.			
thrown from plant)						
			Isolate plant			
Emergency stop (E Stop)			before			
 Service or parking brake 			commencing			
 Battery isolator 			pre-start. Identify			
■ ROPs/FOPs			delineation between site			
Being crushed between			personnel and			
moving parts • Unexpected movement			plant. Apply park			
Neutral Start			brake and			
Reversing/travel alarm			isolation			
Warning horn			procedures to be			
 Amber flashing beacon 			implemented			
 Rear swing warning lights 			when leaving			
 Pedals non slip surface 			cabin			
 Appropriate controls 			Exclusion zones			
Rear view mirror			will be required			
Seat beltDoor inter locks			and a site			
Door inter locksCrush zone decals			specific risk			
 Guarding devices 			assessment			
 Mandatory secondary 			must be			
protection device installed on			undertaken			
all boomtype MEWP			onsite to determine extent			
			of controls			
			High risk			
			Construction			
			work requires			
			the creation and			
			consultation on SWMS –refer to			
			local			
			requirements.			
			·			
			Refer to			
			transport load			
			restraint guide or			
			transport			

Revision No: 1

Issue Date: 4/7/2019



Potential Hazards	ı	Hazaı		Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk Level	New or Additional Controls Action By:	Action Verified as Complete: (Name and
	Υ	N	N/ A				on Plant	Level	(Name and Date)	Date)
					SOP/SWMS to determine proper securing of device.					
5. Can anyone be CUT, STABBED or PUNCTURED? Flying objects Moving parts Pinch points Sharp edges Isolation devices Warning decals Guarding	Y			Potental injury from ejected materials	Pre-start inspection must ensure all guards are in place. Exclusion zones and PPE (goggles, mask, protective clothing) will be required and a risk assessment must be undertaken onsite to determine PPE and controls.					
 6. Can SHEARING occur? Between two moving and rotating parts Between fixed and moving parts Warning decals Guarding 	Y			Body parts can be sheared between two parts of the plant, or plant and structure/obstacle while in operation	Exclusion zones and PPE (goggles, mask, protective clothing) will be required and a risk assessment must be undertaken onsite to determine PPE and controls. Machine must be isolated before cleaning or maintenance					

Revision No: 1

When printed this document is an uncontrolled version and must be checked against the IMS electronic version for validity

Page 6 of 21

When printed this document is an uncontrolled version and must be checked against the IMS electronic version for validity



Potential Hazards	ı	Hazaı		Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk	New or Additional Controls Action	Action Verified as Complete:
	Υ	N	N/ A				on Plant	Level	By: (Name and Date)	(Name and Date)
 7. Can ABRASION, TEARING or STRETCHING occur? Continuous contact with moving parts Warning decals Guarding Pulling/pushing 	Y			Injury caused by contact with moving parts	Exclusion zones and PPE (goggles, mask, protective clothing) will be required and a risk assessment must be undertaken onsite to determine PPE and controls. Machine must be isolated before cleaning or maintenance					
8. Can anyone be STRUCK whilst operating the plant? Plant disintegrating Mobility of plant travelling Reversing/travel alarm Amber flashing beacon Work pieces thrown out Moving parts Warning decals Guarding	Y			Operator and/or workers/public struck by plant and/or debris	Exclusion zones and PPE (goggles, mask, protective clothing) will be required and site specific a risk assessment must be undertaken to determine PPE and controls.					

Revision No: 1 Page 7 of 21



9. Can a hazardous PRESSURE be produced? • Hydraulic hoses • Radiator • Come into contact with fluids under high pressure	Y	Potential Hazard	This item of plant has hydraulic hoses. These hoses must be inspected each day or before each use for wear and tear. I f there are visible signs of wear immediate action must be taken to control the risk arising from this wear. These inspections must be documented. Hydraulic fluid at high pressure can penetrate the skin, never use any part of your body to check for leaks.
			If oil penetrates the skin seek medical advice immediately. Always use a piece of cardboard or
			similar to check for suspected leaks.Hydraulic pressure can be stored and is a hazard. Before disconnection or
			connection of hydraulic hoses complete the following steps - 1. Stop engine 2. Keep all
			bystanders clear of the work area

Revision No: 1



Potential Hazards	ŀ	lazar		Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk	New or Additional Controls Action	Action Verified as Complete:
	Υ	N	N/ A				on Plant	Level	By: (Name and Date)	(Name and Date)
					3. Refer to operators manual as to methods to release pressure					
					4. Wait 5 minutes					
					Ensure that a sturdy, permanent shield is installed to prevent injury due to fluid jet or movement (whiplash) of all hydraulic hoses as a result of fluid leakage or component failure. Once installed this shield(s) must be present and fully functional at all times whilst this item of plant is in operation.					

Revision No: 1 Page 9 of 21

Issue Date: 4/7/2019



10. Can an ELECTRICAL					
• Lack of insulation • Contact with electrical conductors • Poor earthing • Water near equipment • Lack of isolation • Warning decals	Contact wih overhead and/or underground electrical services	Determine location of overhead and underground hazards and clearly mark above ground with minimum approach distances. These distances must be adhered to strictly. Spotters are required when working within 5 metres of the minimum approach distance of any live electrical apparatus. Any encroach within the minimum approach distances must only occur if the following provisions have been met — 1. The machine is designed to work within the minimum approach distances 2. Permission has been granted by the electricity company and 3. Safe systems of work have been			
		been documented and approved.			

Revision No: 1



Potential Hazards	I	Hazaı		Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk	New or Additional Controls Action	Action Verified as Complete:
	Υ	N	N/ A				on Plant	Level	By: (Name and Date)	(Name and Date)
					Establish exclusion zone.					
11. Can an EXPLOSION or LOSS OF CONTENTS occur? Gas emission, Dusts Vapours, lubricants Fuel tank Storage of haz chemicals/DG's near plant Warning decals Ejection of workpiece Collapse or fragmentation	Y			Potential Hazard	Please refer to Operator Manual					
 12. Can anyone using or near the plant SLIP, TRIP or FALL? Uneven surface Fall from a height Weather conditions Slippery surfaces 	Y			Potential Hazard	A site specific risk assessment must be undertaken by client prior to operating plant					
13. Are there ERGONOMIC - MANUAL HANDLING hazards associated with the plant? Poor posture Repetitive or sustained movements Awkward positions Strained movements Poorly designed seating Access and egress Access for maintenance Routine inspections and adjustments	Y			Potential Hazard	Refer to attached Safety Instructions or pages 7-21 of Operator Manual & site specific controls					

Revision No: 1

Issue Date: 4/7/2019

Page 11 of 21



Potential Hazards	tial Hazards Y N N A		N/	Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required on Plant	Final Risk Level	New or Additional Controls Action By: (Name and Date)	Action Verified as Complete: (Name and Date)
14. Are there ERGONOMIC - OPERATING CONTROL hazards associated with the plant?		N	A						(Name and Bate)	Batel
 Difficult to understand Inappropriate colouring Function not identified Inappropriate controls & switches Access and egress Labelling of controls and indicators Variation in operators Operation by two or more persons 										
15. Are there specific requirements for ISOLATION of energy sources?	Y			Potential Hazard	Please refer to Operator Manual					
 Hydraulic pressure Compressed gases Electrical feeds/capacitors Motive power systems Suspended loads Operation by two or more persons 										
16. Can unplanned LOSS of POWER create a hazard?	Y			Potential Hazard	Please refer to Operator Manual					
 Engine shutdown Loss of electrical supply Loss of steering systems Ability to apply brakes and stop Ability to lower suspended loads 										

Revision No: 1

Page 12 of 21



Potential Hazards		Hazaı	rd N/	Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk Level	New or Additional Controls Action By:	Action Verified as Complete: (Name and
	Υ	N	A				on Plant		(Name and Date)	Date)
17. Can anyone be SUFFOCATED?		N								
Lack of oxygenContaminated atmosphereConfined spaces										
Spaces where air flow is inadequate										
18. Does operation of the plant cause extreme TEMPERATURE changes?		N								
 Fire Burns through conduction Convection Cryogenic burns Operation in extreme heat or cold 										
 19. Can a FIRE occur? Friction Ingress of materials/fluids Build-up of materials/lubricants Fuels Fire extinguisher 	Y			Potential Hazard	Fire extinguisher(s) to AS 1841 must be present and fully functional and serviceable at all times. They must be readily accessible to the operator. Regular inspections must also be carried out in accordance with the manufacturer's requirements and AS 1851					

Revision No: 1

When printed this document is an uncontrolled version and must be checked against the IMS electronic version for validity

Issue Date: 4/7/2019



Potential Hazards	ı	Haza	ırd	Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk	New or Additional Controls Action	Action Verified as Complete:
1 otoma nazaras	Υ	N	N/ A	Describe Hazara	Controls	ourient riisk Eever	on Plant	Level	By: (Name and Date)	(Name and Date)
20. Can certain WEATHER conditions create a hazard?	Υ			Potential Hazard	Please refer to Operator Manual					
 Hypothermia / extreme cold Heat stroke / extreme hot Wet conditions Electrical storms Dirt & mud on roads at egress points 										
 21. Does VIBRATION of the plant create a hazard? Plant becomes unstable Causes physical problems for the operator whilst operating 	Y			Potential Hazard to operator over prolonged use	Modify work methods to reduce exposure					
Vibration of equipment Operation could cause unacceptable vibration levels in nearby structures										
22. Can the plant emit toxic FUMES or VAPOURS? Exhaust fumes Chemicals Haz chemicals/DG's	Y			Potential Hazard from exhaust fumes	Do not use in enclosed spaces. Ensure adequate					
23. Carry out NOISE survey	Y			Potential hazard with prolonged	ventilation A site specific					
on page 14. Is the plant noisy? Emit >85 dBA at the operator Effects operator				use	risk assessment must be undertaken to determine PPE and controls.					
communication Noise impacts on community during out-of-hours work (including reversing beepers)										

Revision No: 1 Page 14 of 21



Potential Hazards	ı	Hazaı		Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk	New or Additional Controls Action	Action Verified as Complete:
	Υ	N	N/ A				on Plant	Level	By: (Name and Date)	(Name and Date)
24. Carry out the LIGHT survey on page 14. Is there poor visibility			N/ A							
At the controls At the task Darkens surrounding areas Light impacts on community or sensitive natural environment during out-of-hours work										
25. Does the plant emit RADIATION?		N								
■ Eg X-rays ■ EMR ■ Laser										
26. Can operation of the plant create DUST? Explosive atmosphere Breathing hazard Reduced visibility Nuisance dust at nearby community Impact on local flora and fauna Loss of topsoil and spread of weeds and pathogens	Y			Exposure to hazardous dust	Site risk assessment must be undertaken by client to ensure hazardous dust is not disturbed by plant/task (e.g. asbestos) Exclusion zones and PPE (goggles, mask, protective clothing) will be required and a risk assessment must be undertaken onsite to determine PPE and controls					

Revision No: 1 Page 15 of 21

Issue Date: 4/7/2019



Potential Hazards	ı	Hazard		Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk Level	New or Additional Controls Action By:	Action Verified as Complete: (Name and
	Υ	N	N/ A				on Plant	Level	(Name and Date)	Date)
27. Can the plant become UNSTABLE during operation? Working on uneven / unstable ground Shifting load Lack of plant support Outriggers	Y			Potential Hazard	A site specific risk assessment must be undertaken by client onsite to determine PPE and controls					
28. Could LOSS of LOAD occur? Failure of ropes/slings Overloading Entanglement in surrounding structures Maintenance requirements	Y			Potential Hazard	Refer to Operator manual for pre- operational checks, maintenance & load capacity					
29. Is there anything in the SURROUNDING ENVIRONMENT that may produce a hazard? Power lines Low ceiling Other plant Storage areas Co-located equipment Isolation requirements Potential for flash flooding if operating adjacent to waterways Operating in known areas of weeds, pathogens or contamination Operating in sensitive environments requiring protection from offsite weeds/pathogens or spills	Y			Potential Hazard	A site specific risk assessment must be undertaken by client to determine controls, PPE & exclusion zones.					

Revision No: 1 Page 16 of 21



Potential Hazards	Hazard		ď	Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk	New or Additional Controls Action	Action Verified as Complete:
	Υ	N	N/ A				on Plant	Level	By: (Name and Date)	(Name and Date)
 30. Can CHEMICALS create a hazard? Leaking from plant Splashing Explosion PPE considerations Spill kit considerations 	Y			Potential Hazard	Please refer to Operator Manual.					

Revision No: 1

When printed this document is an uncontrolled version and must be checked against the IMS electronic version for validity



31. Operator TRAINING /						
QUALIFICATIONS? Training requirements Qualification requirements Competency assessments Documentation Operator's manual Equipment experience	Y	Operation by persons who are not suitably qualified or experienced may result in injury to person, damage to property, and may also void insurance cover.	This equipment may only be moved and operated by persons who meet the following requirements:			
Product knowledge			 18 years or older. 			
			 Physically and mentally suited for this work. 			
			• Persons have been instructed in driving and servicing the earth moving machinery and have proven their qualifications to the owner/contractor			
			 Persons are expected to perform work reliably. 			
			Persons who have been appointed by the contractor for driving and servicing the earth moving machinery.			
			• They are informed on and follow the legal regulations of the relevant authority.			
			All operators must completely read and			

Revision No: 1

Page 18 of 21



Potential Hazards	ŀ	Hazard		Describe Hazard	Controls	Current Risk Level	New or Additional Controls Required	Final Risk	New or Additional Controls Action	Action Verified as Complete:
	Υ	N	N/ A				on Plant	Level	By: (Name and Date)	(Name and Date)
					understand the Operator Manual prior to operating plant.					
					Undertake a Job Safety and Environmental Analysis before use of plant, and use to determine that the relevant safety procedures are in place before commencing work.					
32. Are there ANY OTHER potential hazards generated by or during the use of this item of plant and/or any attachments?	Y			Plant Failure	Pre – Operational Inspection	D	DAILY - Operators must complete Start-up checklist Operation checklist Parking Checklist	Е		

ALL OPERATORS OF THE PLANT OR EQUIPMENT MUST BE BRIEFED ON THE PLANT HAZARD ASSESSMENT (PHA) PRIOR TO FIRST TIME USE.

ANY RELEVANT CONDITIONS WHICH MAY IMPACT ON THE OPERATION OF THIS ITEM OF PLANT OR EQUIPMENT MUST BE TRANSFERRED TO THE AMS/TRA.

Revision No: 1 Page 19 of 21



NOISE REPORT			
Equipment Type:	Twin Drum Roller	Serial/Asset No.	1NT6YT
Make:	Dynapac	Model:	CC1200vi
Test by (print):	Leigh Evans	Date:	18/3/20
Signature:			
Sound Level Meter Ur	nit Used:		
Manufactures specifie	ed noise level:		102 dBA
Background level:			85.6dBA
Results - Operator's		102	dBA High Idle
(Equipment Operating	a)	102	dBA Low Idle
Comments:		1	
Results – Bystander F At 7 metres from side		mont Operating (His	sh Idlo)
Front	or equipment – Equip	The intoperating (ring	dBA
Rear			dBA
Left			dBA
Right			dBA
Comments:			UDA
Comments.			

LIGHTING REPORT				
Test by (print):		Date:		
Signature:				
Lux Meter used:				
Results - Operator's station				
At controls				Lux
At emergency control				Lux
In front/over task				Lux
Left side task				Lux
Right side task				Lux
Comments:				
Results - Surroundings:				
Clearly seen by others?		□ Yes	□ No	
Decrease lighting in walkways	?	□ Yes	□ No	
Decrease lighting to other wor	kstations?	□ Yes	□ No	
Comments:				

Revision No: 1

Page 20 of 21



COMMENTS:

Revision No: 1

Page 21 of 21