

SPECIFICATIONS

GR-15		
Height, working maximum	20 ft 8 in	6.30 m
Height, platform maximum	14 ft 8 in	4.47 m
Height, stowed maximum	62 in	1.57 m
Height, stowed maximum standard platform with work station tray	64 in	1.62 m
Height, stowed maximum stock picker platform with work station tray	64 in	1.62 m
Height, stowed maximum stock picker platform with bike racks	63 in	1.60 m
Width	29.5 in	75 cm
Length, stowed	53 in	1.35 m
Length with standard platform optional platform extension extended	73.3 in	1.85 m
Length with stock picker platform including adjustable tray	73.8 in	1.87 m
Length with stock picker platform including adjustable tray and work station tray	75.1 in	1.91 m
Maximum capacity, standard platform	500 lbs	227 kg
Maximum capacity, AWP and fiberglass platform	350 lbs	159 kg
Maximum capacity, stock picker platform	500 lbs	227 kg
Maximum wind speed	28 mph	12.5 m/s
Turning radius (inside)	0 in	0 cm
Turning radius (outside)	31 in	78.7 cm
Weight (Machine weights vary with option configurations)	See Serial Label	

Power source	4 Batteries, 6V 225AH	
Controls	Proportional	
AC outlet in platform	Standard	
Tire size	10 x 3 x 1 in 25.4 x 7.6 x 2.5 cm	
Airborne noise emissions Maximum sound level at normal operating workstations (A-weighted)	70 dB	
Maximum slope rating, stowed position	30% (17°)	
Maximum side slope rating	30% (17°)	
Note: Slope rating is subject to ground conditions and adequate traction.		

Drive speeds

Stowed, maximum	2.5 mph 40 ft/10.9 sec	4.0 km/h 12.2 m/10.9 sec
Platform raised, maximum	0.5 mph 40 ft/55 sec	0.8 km/h 12.5 m/55 sec

Floor loading information

Tire load, maximum	1337 lbs	606 kg
Tire contact pressure	205.7 psi	14.4 kg/cm ² 1418 kPA
Occupied floor pressure	248 psf	1210 kg/m ² 11.87 kPA

Note: Floor loading information is approximate and does not incorporate different option configurations. It should be used only with adequate safety factors.

Continuous improvement of our products is a Genie policy. Product specifications are subject to change without notice or obligation.

SPECIFICATIONS

GR-20		
Height, working maximum	25 ft 11 in	7.90 m
Height, platform maximum	19 ft 11 in	6.07 m
Height, stowed maximum	78 in	1.98 m
Height, stowed maximum stock picker platform with bike racks	63.2 in	1.60 m
Width	31.5 in	80 cm
Length, stowed	53 in	1.35 m
Length with standard platform optional platform extension extended	73.3 in	1.86 m
Length with stock picker platform including adjustable tray	73.8 in	1.87 m
Maximum capacity, standard platform	350 lbs	159 kg
Maximum capacity, AWP and fiberglass platform	350 lbs	159 kg
Maximum capacity, stock picker platform	350 lbs	159 kg
Maximum wind speed	28 mph	12.5 m/s
Turning radius (inside)	0 in	0 cm
Turning radius (outside)	31 in	78.7 cm
Weight (Machine weights vary with option configurations)	See Serial Label	
Power source	4 Batteries, 6V 225AH	
Controls	Proportional	

AC outlet in platform	Standard	
Tire size	10 x 3 x 1 in 25.4 x 7.6 x 2.5 cm	
Airborne noise emissions Maximum sound level at normal operating workstations (A-weighted)	70 dB	
Maximum slope rating, stowed position	30% (17°)	
Maximum side slope rating	30% (17°)	

Note: Slope rating is subject to ground conditions and adequate traction.

Drive speeds

Stowed, maximum	2.5 mph 40 ft/10.9 sec	4.0 km/h 12.2 m/10.9 sec
Platform raised, maximum	0.5 mph 40 ft/55 sec	0.8 km/h 12.5 m/55 sec

Floor loading information

Tire load, maximum	1219 lbs	553 kg
Tire contact pressure	187.5 psi	13 kg/cm ² 1292.76 kPA
Occupied floor pressure	241.6 psf	1180 kg/m ² 11.57 kPA

Note: Floor loading information is approximate and does not incorporate different option configurations. It should be used only with adequate safety factors.

Continuous improvement of our products is a Genie policy. Product specifications are subject to change without notice or obligation.

SPECIFICATIONS

Platform dimensions, all models (length x width)

Standard platform	35 x 29.5 in	88 x 75 cm
Standard platform with extension	55 x 29.5 in	1.4 m x 75 cm
Stock picker platform	35 x 28.8 in	88 x 73 cm
Stock picker platform including adjustable tray	56 x 28.8 in	1.4 m x 73 cm
Standard AWP platform	27 x 26 in	69 x 51 cm
Narrow AWP platform	26 x 20 in	66 cm x 51 cm
Standard fiberglass platform	29 x 26.5 in	74 x 67 cm
Narrow fiberglass platform	26 x 22 in	66 x 56 cm