

## SPECIFICATIONS

| <b>GR-15</b>   |   |          |
|--|---|----------|
| Height, working maximum  | 20 ft 8 in  | 6.30 m   |
| Height, platform maximum   | 14 ft 8 in  | 4.47 m   |
| Height, stowed maximum   | 62 in   | 1.57 m   |
| Height, stowed maximum<br>standard platform with work station tray                   | 64 in   | 1.62 m   |
| Height, stowed maximum<br>stock picker platform with work station tray               | 64 in   | 1.62 m   |
| Height, stowed maximum<br>stock picker platform with bike racks                      | 63 in   | 1.60 m   |
| Width  | 29.5 in   | 75 cm    |
| Length, stowed   | 53 in   | 1.35 m   |
| Length with standard platform<br>optional platform extension extended                | 73.3 in   | 1.85 m   |
| Length with stock picker platform<br>including adjustable tray                       | 73.8 in   | 1.87 m   |
| Length with stock picker platform<br>including adjustable tray and work station tray | 75.1 in   | 1.91 m   |
| Maximum capacity,<br>standard platform   | 500 lbs   | 227 kg   |
| Maximum capacity,<br>AWP and fiberglass platform                                     | 350 lbs   | 159 kg   |
| Maximum capacity,<br>stock picker platform   | 500 lbs   | 227 kg   |
| Maximum wind speed   | 28 mph  | 12.5 m/s |
| Turning radius (inside)  | 0 in  | 0 cm     |
| Turning radius (outside)   | 31 in   | 78.7 cm  |
| Weight   | See Serial Label<br>(Machine weights vary with option configurations) |          |

|   |                                      |  |
|---|--------------------------------------|--|
| Power source  | 4 Batteries, 6V 225AH                |  |
| Controls  | Proportional                         |  |
| AC outlet in platform   | Standard                             |  |
| Tire size   | 10 x 3 x 1 in<br>25.4 x 7.6 x 2.5 cm |  |
| Airborne noise emissions  | 70 dB                                |  |
| Maximum sound level at normal operating workstations<br>(A-weighted)      |                                      |  |
| Maximum slope rating, stowed position                                     | 30% (17°)                            |  |
| Maximum side slope rating   | 30% (17°)                            |  |
| Note: Slope rating is subject to ground conditions and adequate traction. |                                      |  |

**Drive speeds**

|                          |                           |                             |
|--------------------------|---------------------------|-----------------------------|
| Stowed, maximum          | 2.5 mph<br>40 ft/10.9 sec | 4.0 km/h<br>12.2 m/10.9 sec |
| Platform raised, maximum | 0.5 mph<br>40 ft/55 sec   | 0.8 km/h<br>12.5 m/55 sec   |

**Floor loading information**

|                         |           |                                     |
|-------------------------|-----------|-------------------------------------|
| Tire load, maximum      | 1337 lbs  | 606 kg                              |
| Tire contact pressure   | 205.7 psi | 14.4 kg/cm <sup>2</sup><br>1418 kPA |
| Occupied floor pressure | 248 psf   | 1210 kg/m <sup>2</sup><br>11.87 kPA |

Note: Floor loading information is approximate and does not incorporate different option configurations. It should be used only with adequate safety factors.

Continuous improvement of our products is a Genie policy. Product specifications are subject to change without notice or obligation.

## SPECIFICATIONS

| <b>GR-20</b>  |                       |          |
|---|-----------------------|----------|
| Height, working maximum   | 25 ft 11 in           | 7.90 m   |
| Height, platform maximum  | 19 ft 11 in           | 6.07 m   |
| Height, stowed maximum  | 78 in                 | 1.98 m   |
| Height, stowed maximum<br>stock picker platform with bike racks       | 63.2 in               | 1.60 m   |
| Width   | 31.5 in               | 80 cm    |
| Length, stowed  | 53 in                 | 1.35 m   |
| Length with standard platform<br>optional platform extension extended | 73.3 in               | 1.86 m   |
| Length with stock picker platform<br>including adjustable tray        | 73.8 in               | 1.87 m   |
| Maximum capacity,<br>standard platform                                | 350 lbs               | 159 kg   |
| Maximum capacity,<br>AWP and fiberglass platform                      | 350 lbs               | 159 kg   |
| Maximum capacity,<br>stock picker platform                            | 350 lbs               | 159 kg   |
| Maximum wind speed  | 28 mph                | 12.5 m/s |
| Turning radius (inside)   | 0 in                  | 0 cm     |
| Turning radius (outside)  | 31 in                 | 78.7 cm  |
| Weight<br>(Machine weights vary with option configurations)           | See Serial Label      |          |
| Power source  | 4 Batteries, 6V 225AH |          |
| Controls  | Proportional          |          |

|  |                                      |  |
|--|--------------------------------------|--|
| AC outlet in platform  | Standard                             |  |
| Tire size  | 10 x 3 x 1 in<br>25.4 x 7.6 x 2.5 cm |  |
| Airborne noise emissions<br>Maximum sound level at normal operating workstations<br>(A-weighted) | 70 dB                                |  |
| Maximum slope rating, stowed position  | 30% (17°)                            |  |
| Maximum side slope rating  | 30% (17°)                            |  |

Note: Slope rating is subject to ground conditions and adequate traction.

**Drive speeds**

|                          |                           |                             |
|--------------------------|---------------------------|-----------------------------|
| Stowed, maximum          | 2.5 mph<br>40 ft/10.9 sec | 4.0 km/h<br>12.2 m/10.9 sec |
| Platform raised, maximum | 0.5 mph<br>40 ft/55 sec   | 0.8 km/h<br>12.5 m/55 sec   |

**Floor loading information**

|                         |           |                                      |
|-------------------------|-----------|--------------------------------------|
| Tire load, maximum      | 1219 lbs  | 553 kg                               |
| Tire contact pressure   | 187.5 psi | 13 kg/cm <sup>2</sup><br>1292.76 kPA |
| Occupied floor pressure | 241.6 psf | 1180 kg/m <sup>2</sup><br>11.57 kPA  |

Note: Floor loading information is approximate and does not incorporate different option configurations. It should be used only with adequate safety factors.

Continuous improvement of our products is a Genie policy. Product specifications are subject to change without notice or obligation.

## SPECIFICATIONS

**Platform dimensions, all models (length x width)**

|   |              |               |
|---|--------------|---------------|
| Standard platform                               | 35 x 29.5 in | 88 x 75 cm    |
| Standard platform with extension                | 55 x 29.5 in | 1.4 m x 75 cm |
| Stock picker platform                           | 35 x 28.8 in | 88 x 73 cm    |
| Stock picker platform including adjustable tray | 56 x 28.8 in | 1.4 m x 73 cm |
| Standard AWP platform                           | 27 x 26 in   | 69 x 51 cm    |
| Narrow AWP platform                             | 26 x 20 in   | 66 cm x 51 cm |
| Standard fiberglass platform                    | 29 x 26.5 in | 74 x 67 cm    |
| Narrow fiberglass platform                      | 26 x 22 in   | 66 x 56 cm    |